

Dane techniczne

| Typ | PO – 50 | PO-85 | PO-100 | PO-150 |
|-------------------|---------------|---------------|---------------|---------------|
| Moc cieplna | 50 kW | 85 kW | 105 kW | 150 |
| Zakres mocy kW | 30 –65 kW | 75 – 95 | 95 –115 | 110-150 |
| Poj. wodna kotła | 165 l | 340 l | 360 l | 390 l |
| Śred. Wyl. spalin | 200 | 200 | 200 | 200 |
| Wymiary L x B x H | 1240x780x1170 | 1380x780x1420 | 1380x780x1420 | 1450x780x1520 |
| Podl. Zasil/pow | DN 50 | DN 65 | DN 65 | DN 65 |
| Ciężar | 360 kg | 480 kg | 568 kg | 686 kg |
| Sprawność | 90% | 90% | 90% | 90% |
| Zasilania | 220 V / 50 Hz | 220 V / 50 Hz | 220 V / 50 Hz | 220/50Hz |
| Pobór prądu | 2,8 A | 2,8 A | 3,3 A | 3,3 A |
| Zużycie oleju | 4,6 kg/h | 7,0 kg/h | 10,2 kg/h | 14,0 kg/h |
| Palnik typ | CBW-50 | CBW-50 | CBW-100 | CBW-150 |

